
CUSTOMER:HLK P/N:HLK-315 品名规格:防水头 Z款系列 2PIN-公 REV. / APPROVE: REVISIONS DESCRIPTION **REACH** COMPLIANT DATE





<u>+</u>	±0.7	±0.6	±0.4	±0.2	公差范围
角度	>30	20-30	10-20	0-10	尺寸要求

	THE INFO	±0.2	- > >			0-10			
	RMATION CO	±0.4 ±0.6			0-10 10-20 20-30 >30				
	ONTAINED HE	±0.6		20-30					
	EREIN IS PF	±0./			>30				
	ROPRIETARY	H		角度					
	TO HONLIN								
	K. ANY USE								
	OR DISCL								
	THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO HONLINK. ANY USE OR DISCLOSURE OF THIS INFORMATION, EXCEPT FOR THE EXCLUSIVE BENEFIT OF HONLINK IS PROHIBITED.								
		DRAWN BY:	[FNGINFFR RY		PRODUCTION BY	QUALITY BY:		MANAGER BY:
			:	₽ 		DN BY	Υ: _		BY:
		VALLEY							
		DW		UNIT:		PRODU		HONLINK	
		DWG NO: HLK-315		mm		PRODUCT NO:N/A			w
	OF HONLINI	HLK-3						HTH.	NLINK ELECTR
	IK IS PROH	315		SHEET:			//	NOH WWW/	NICIAN TECHNO
	BITED.			SHEET: 1 OF 1		DATE: 2021.10.06		HTTP: //www.HONI INKGROLIP COM	HONLINK ELECTRICIAN TECHNOLOGY(KUN SHAN) CO.,LTD
		0		REV.		.10.06		_	√) co.,LTD