

Brand:	HONLIX
P/N:	HLK-506
MOQ:	500PCS/PER
Place of Origin:	Kunshan City,China
Delivery Time:	1 week
Start Port:	Shanghai
General Features:	
Product Name	40A charge and discharge connector
Product Spec	3+10PIN Female
Connector locking system	N/A
Degree of protection	IP65
Ambient temperature(operation)	-25°C~+85°C
Customs tariff number	8536901900
Environmental compliance	RoHs, Reach
Electrical Parameters:	
Rated voltage	48V
Rated current(25°C)	40A
Withstand voltage	500V
Contact resistance	≤10mΩ
Insulation resistance	≥20MΩ
Mechanical Performance:	
Mechanical operation	≤3000 mating cycles
Insertion force	≤20N
Pull out force	≥3N
Wiring range	0.2m ² ~8m ²
Application Area	
Signal&Power contal and transmission of E-motorcycle	

品牌:	HONLINK
料号:	HLK-506
起订量:	500PCS/PER
产地:	Kunshan City,China
交货周期:	1 week
发货港:	Shanghai

一般特性:	
产品名称	40A 充放电连接器
产品规格	3+10PIN 母
连接器互锁方式	N/A
防护等级	IP65
使用环境	-25°C~+85°C
海关编码	8538900000
环保等级	RoHs, Reach
电气参数:	
电压等级	48V
额定电流(25°C)	40A
耐电压	500V
接触电阻	≤10mΩ
绝缘电阻	≥20MΩ
机械参数:	
插拔寿命	≤3000 mating cycles
插入力	≤20N
拔出力	≥3N
配线范围	0.2m2~8m2
应用领域:	
电动摩托车电源,信号控制及传输	