

Brand:	<b>HONLIX</b>
P/N:	HLK-607-1
MOQ:	500PCS/PER
Place of Origin:	Kunshan City,China
Delivery Time:	1 week
Start Port:	Shanghai
<b>General Features:</b>	
Product Name	20A 32A 40A 50A 60A 80A GB DC Charging gun/直流充电枪
Product Spec	2+1+5 PIN Male
Connector locking system	N/A
Degree of protection	IP55
Ambient temperature(operation)	-25°C~+85°C
Customs tariff number	8427109000
Environmental compliance	RoHs, Reach
<b>Electrical Parameters:</b>	
Rated voltage	750V / 1000V DC
Rated current(25°C)	20A 32A 40A 50A 60A 80A
Withstand voltage	3500V
Contact resistance	≤0.5mw Max
Insulation resistance	≥500MΩ
<b>Mechanical Performance:</b>	
Mechanical operation	≤10000 mating cycles
Insertion force	< 100N
Pull out force	< 100N
Wiring range	20A-2*4+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 22.5mm 32A-2*6+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 25.5mm 40A-2*8+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 24.5mm 50A-2*10+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 24.0mm 60A-2*16+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 23.5mm 80A-2*16+1*2.5+2*1.5+(2*0.75)(P2)+5*0.75+(3*0.75)(P2), 22.5mm
<b>Application Area</b>	
Electric vehicles that comply with China GB charging standards	