

2 系_储能连接解决方案

2 Series_Energy Storage Connectivity Solutions



公司简介 Company Profile

弘林科创建于2015年，是全球知名的大功率连接器整体方案提供商，拥有ISO9001, ISO14001, IATF16949管理体系认证，通过了CE RoHS REACH等国际测试认证，同时也获得中国国家知识产权局授权专利约30项左右，是中国国家科技型创新企业，弘林科在全球拥有2个制造工厂（分别位于中国昆山/河南南阳），5个销售公司（中国/日本/泰国/韩国/美国）

弘林科拥有资深专业的模具设计加工，自动化制造能力，完整的检测设备及技术，打造全球一流的连接器品牌，服务全球用户；同时我们具有强大的定制化能力，依据不同客户的差异化需求，提供专业，高效，快捷的定制化连接解决方案，为顾客创造价值。

弘林科专注于新能源连接器，其中1系_M5/M8/M12/M16圆型连接器，2系_储能连接器，3系_电动自行车连接器，4系_电动工具连接器，5系_电动摩托车连接器，6系电动汽车充电枪/座，7系充电桩及放电枪等一站式解决方案。

Founded in 2015, Honlix is a world-renowned total solution provider of high power connectors with ISO9001, ISO14001, IATF16949 management system certification, passed CE RoHS REACH and other international testing and certification, and also obtained about 30 patents authorized by China National Intellectual Property Patent Office, which is a national science and technology-based innovative enterprise in China.

Honlix has 2 manufacturing factories (located in Kunshan, China / Nanyang, Henan Province) and 5 sales companies (China / Japan / Thailand / Korea / USA)

Honlix has experienced and professional mold design and processing, automated manufacturing capabilities, complete testing equipment and technology to build a global first-class connector brand to serve the global user; at the same time, we have a strong ability to customize, according to the different customer needs, to provide professional, efficient, and effective connectors to meet different needs. At the same time, we have a strong customization ability, according to the differentiated needs of different customers, to provide professional, efficient, fast customized connection solutions, to create value for customers.

Honlix specializes in new energy connectors, including Series 1_M5/M8/M12/M16 circular connectors, Series 2_energy storage connectors, Series 3_electric bicycle connectors, Series 4_electric tool connectors, Series 5_electric motorcycle connectors, Series 6_electric vehicle charging guns/mounts, Series 7 charging piles and discharging guns, and other one-stop solutions.

HONLIX

**Honlix's HQ
In Kunshan China**



**COMMING
SOON**

**NEW
HQ_2026**

honlix.com

Ownership of HQ

www.honlix.com

公司简介 Company Profile



昆山工厂
Kunshan Factory



河南工厂
Henan Factory

资质证书 Certificates



ISO90001



ISO14000



TS16949



CE



RoHs




CE



Utility model patents



Appearance Patent



EIA report

全球服务 Global Services

HONLIX



1. Kunshan, China_factory
2. Henan, China_factory
3. Shanghai, China_office
4. Yokohama, Japan_office
5. Seoul, Korea_office
6. California, USA_office
7. Bangkok, Thailand_office

1. 中国昆山_工厂
2. 中国河南_工厂
3. 中国上海_销售办公室
4. 日本横滨_销售办公室
5. 韩国首尔_销售办公室
6. 美国加州_销售办公室
7. 泰国曼谷_销售办公室

储能连接器应用 Energy Storage Connectors Application

6.0 Male




6.0 Female



Terminal block



Start-Stop Battery Terminal



2系_产品目录
2 Series_Contents

1. $\varphi 6.0$ 120A Single Core Energy Storage Connectors

HLK-201 $\varphi 6.0$ Male	1
HLK-202 $\varphi 6.0$ Female	2

1. $\varphi 8.0$ 200A Single Core Energy Storage Connectors

HLK-203 $\varphi 8.0$ Male	3
HLK-204 $\varphi 8.0$ Female	4

HLK-201

- $\varnothing 6.0$ 公
- $\varnothing 6.0$ Male

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|---|--------------------------|-----------------------|
| • 额定电流: | 120A | • 端子接线方式: | 铆压 |
| • Rated current: | 120A | • Terminal Connection: | Riveting and pressing |
| • 额定电压: | 1000V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 1000V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | $\geq 500M\Omega$ | • 耐电压 : | 3000V AC |
| • Insulation resistance: | $\geq 500M\Omega$ | • Withstand voltage : | 3000V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥ 3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥ 3000 cycles |
| • 使用环境: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • 拔出力: | $\geq 2\text{N}$ |
| • Operating temperature: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • Pull-out force: | $\geq 2\text{N}$ |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-201 download online
www.honlix.com

推荐面板安装尺寸
 Recommended Panel Mounting Dimensions

HLK-202

- $\varnothing 6.0$ 母
- $\varnothing 6.0$ Female

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size






技术参数 Technical Data

- | | | | |
|--------------------------|---|--------------------------|-----------------------|
| • 额定电流: | 120A | • 端子接线方式: | 铆压 |
| • Rated current: | 120A | • Terminal Connection: | Riveting and pressing |
| • 额定电压: | 1000V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 1000V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | $\geq 500M\Omega$ | • 耐电压 : | 3000V AC |
| • Insulation resistance: | $\geq 500M\Omega$ | • Withstand voltage : | 3000V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥ 3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥ 3000 cycles |
| • 使用环境: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • 拔出力: | $\geq 2N$ |
| • Operating temperature: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • Pull-out force: | $\geq 2N$ |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-202 download online
www.honlix.com

推荐面板安装尺寸
 Recommended Panel Mounting Dimensions

HLK-203

- $\varnothing 8.0$ 公
- $\varnothing 8.0$ Male

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|---|--------------------------|-----------------------|
| • 额定电流: | 200A | • 端子接线方式: | 铆压 |
| • Rated current: | 200A | • Terminal Connection: | Riveting and pressing |
| • 额定电压: | 1000V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 1000V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | $\geq 500M\Omega$ | • 耐电压 : | 3000V AC |
| • Insulation resistance: | $\geq 500M\Omega$ | • Withstand voltage : | 3000V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥ 3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥ 3000 cycles |
| • 使用环境: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • 拔出力: | $\geq 2\text{N}$ |
| • Operating temperature: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • Pull-out force: | $\geq 2\text{N}$ |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-203 download online
www.honlix.com

推荐面板安装尺寸
 Recommended Panel Mounting Dimensions

HLK-204

- $\varnothing 8.0$ 公
- $\varnothing 8.0$ Male

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size






技术参数 Technical Data

- | | | | |
|--------------------------|---|--------------------------|-----------------------|
| • 额定电流: | 200A | • 端子接线方式: | 铆压 |
| • Rated current: | 200A | • Terminal Connection: | Riveting and pressing |
| • 额定电压: | 1000V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 1000V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | $\geq 500M\Omega$ | • 耐电压 : | 3000V AC |
| • Insulation resistance: | $\geq 500M\Omega$ | • Withstand voltage : | 3000V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥ 3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥ 3000 cycles |
| • 使用环境: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • 拔出力: | $\geq 2N$ |
| • Operating temperature: | $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ | • Pull-out force: | $\geq 2N$ |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-204 download online
www.honlix.com

推荐面板安装尺寸
 Recommended Panel Mounting Dimensions

HLK-207

- 菱形100A 双螺纹 H59/PA66 2*M5 孔距21mm
- Diamond 100A Double Thread H59/PA66 2*M5 Hole Distance 21mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size

技术参数 Technical Data

- 额定电流: 100A
- Rated current: 100A
- 额定电压: 600V DC
- Rated voltage: 600V DC
- 绝缘电阻: $\geq 500M\Omega$
- Insulation resistance: $\geq 500M\Omega$
- 阻燃等级: UL94V-0
- Flame retardant rating: UL94V-0
- 使用环境: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- 防护等级: N/A
- IP grade: N/A





- 端子接线方式: 锁螺丝
- Terminal Connection: Locking screw
- 盐雾测试: 48 H
- Salt spray resistance: 48 H
- 耐电压: 1000V DC
- Withstand voltage: 1000V DC
- 机械寿命: ≥ 3000 次
- Flame retardant rating: ≥ 3000 cycles
- 中心孔紧固力: $\geq 9\text{N Max}$
- Locking force: $\geq 9\text{N Max}$
- 环保等级: RoHS
- Environmental grade: RoHS

商务条款 Terms of business

- 起订量: 1 pcs
- MOQ: 1 pcs
- 交货周期: 2周 (紧急订单1周)
- L/T: 2 weeks

- 交货条款: Ex works
- Terms of delivery: Ex works
- 海关编码: 854422100
- HS code: 854422100

产品尺寸 Product dimension



HLK-207 download online
www.honlix.com

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-208

- 菱形150A 双螺纹 H62/PA66 2*M4 孔距40mm
- Diamond 150A Double Thread H62/PA66 2*M4 Hole Distance 40mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 150A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 150A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸
Recommended Panel Mounting Dimensions

[HLK-208 download online
www.honlix.com](http://www.honlix.com)

HLK-209

- 菱形150A 单螺纹 H62/PA66 2*M4 孔距40mm
- Diamond 150A Signal Thread H62/PA66 2*M4 Hole Distance 40mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 150A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 150A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-209 download online
www.honlix.com](http://www.honlix.com)

HLK-210

- 菱形300A 双螺纹 H62/PA66 2*M4 孔距44mm
- Diamond 300A Signal Thread H62/PA66 2*M4 Hole Distance 44mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size

技术参数 Technical Data

- 额定电流: 300A
- Rated current: 300A
- 额定电压: 600V DC
- Rated voltage: 600V DC
- 绝缘电阻: $\geq 500M\Omega$
- Insulation resistance: $\geq 500M\Omega$
- 阻燃等级: UL94V-0
- Flame retardant rating: UL94V-0
- 使用环境: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- 防护等级: N/A
- IP grade: N/A



- 端子接线方式: 锁螺丝
- Terminal Connection: Locking screw
- 盐雾测试: 48 H
- Salt spray resistance: 48 H
- 耐电压: 1000V DC
- Withstand voltage: 1000V DC
- 机械寿命: ≥ 3000 次
- Flame retardant rating: ≥ 3000 cycles
- 中心孔紧固力: $\geq 9\text{N Max}$
- Locking force: $\geq 9\text{N Max}$
- 环保等级: RoHS
- Environmental grade: RoHS

商务条款 Terms of business

- 起订量: 1 pcs
- MOQ: 1 pcs
- 交货周期: 2周 (紧急订单1周)
- L/T: 2 weeks

- 交货条款: Ex works
- Terms of delivery: Ex works
- 海关编码: 854422100
- HS code: 854422100

产品尺寸 Product dimension



开孔尺寸
Hole Size

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

[HLK-210 download online
www.honlix.com](http://www.honlix.com)

HLK-211

- 菱形500A 双螺纹 紫铜/PA66 2*M4 孔距44mm
- Diamond 500A Signal Thread Red Copper/PA66 2*M4 Hole Distance 44mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 500A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 500A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-211 download online
www.honlix.com

HLK-212

- 方形100A 双螺纹，H62/PA66 孔距20*20mm
- Square 100A Double Thread H62/PA66 Hole Pitch 20*20mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 100A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 100A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



开孔尺寸
Hole Size

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

[HLK-212 download online
www.honlix.com](http://www.honlix.com)

HLK-213

- 方形100A 单螺纹, H62/PA66 孔距20*20mm
- Square 100A Signal Thread H62/PA66 Hole Pitch 20*20mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 100A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 100A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-213 download online
www.honlix.com](http://www.honlix.com)

HLK-214

- 方形120A 双螺纹，H62/PA66 孔距20*20mm
- Square 120A Double Thread H62/PA66 Hole Pitch 20*20mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 120A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 120A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

HLK-214 download online
www.honlix.com

HLK-215

- 方形120A 单螺纹，H62/PA66 孔距20*20mm
- Square 120A Signal Thread H62/PA66 Hole Pitch 20*20mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 120A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 120A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-215 download online
www.honlix.com](http://www.honlix.com)

HLK-216

- 方形 200A 双螺纹，H62/PA66 孔距23*23mm
- Square 200A Double Thread H62/PA66 Hole Pitch 23*23mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 200A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 200A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-216 download online
www.honlix.com

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-217

- 方形 200A 单螺纹, H62/PA66 孔距23*23mm
- Square 200A Signal Thread H62/PA66 Hole Pitch 23*23mm

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 200A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 200A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周（紧急订单1周） | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



开孔尺寸
Hole Size

推荐面板安装尺寸

Recommended Panel Mounting Dimensions

HLK-217 download online
www.honlix.com

HLK-218

- 方形 200A 双螺纹，H62/PA66 孔距23*23mm_外贸专供
- Square 200A Double Thread H62/PA66 Hole Pitch 23*23mm_Global customization

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 200A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 200A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-218 download online](http://www.honlix.com)
www.honlix.com

HLK-219

- 方形 200A 单螺纹，H62/PA66 孔距23*23mm_外贸专供
- Square 200A Signal Thread H62/PA66 Hole Pitch 23*23mm_Global customization

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 性价比极高
- Excellent value
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 200A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 200A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-219 download online](http://www.honlix.com)
www.honlix.com

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-220

- 强启 方形 250A 圆锥双螺纹 H62/PA66 孔距23*23
- Qiangqi Square 250A Tapered Double Thread H62/PA66 Hole Pitch 23*23

应用领域 Application Areas

- 启停电源与通讯连接传输
- Start-stop power and communication connection transmission

产品功能特点 Product Points

- 支持瞬间大电流使用场景
- Supports instantaneous high current usage scenarios
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 250A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 250A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



负极/Negative pole
推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-220 download online
www.honlix.com

HLK-221

- 强启 方形 250A 综合单螺纹 H62/PA66 孔距23*23
- Qiangqi Square 250A Tapered Signal Thread H62/PA66 Hole Pitch 23*23

应用领域 Application Areas

- 启停电源与通讯连接传输
- Start-stop power and communication connection transmission

产品功能特点 Product Points

- 支持瞬间大电流使用场景
- Supports instantaneous high current usage scenarios
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 250A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 250A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



负极/Negative pole
推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-221 download online
www.honlix.com

HLK-222

- 方形 300A 双螺纹 H62/PA66 孔距33*33
- Square 300A Double Thread H62/PA66 Hole Pitch 33*33

应用领域 Application Areas

- 启停电源与通讯连接传输
- Start-stop power and communication connection transmission

产品功能特点 Product Points

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 300A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 300A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



开孔尺寸
Hole Size

推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-222 download online
www.honlix.com](http://www.honlix.com)

HLK-223

- 方形 300A 单螺纹 H62/PA66 孔距33*33
- Square 300A Signal Thread H62/PA66 Hole Pitch 33*33

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 支持瞬间大电流使用场景
- Supports instantaneous high current usage scenarios
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size


技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 300A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 300A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |


商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-223 download online
www.honlix.com



推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-224

- 方形 500A 双螺纹 紫铜/PA66 孔距33*33
- Square 300A Double Thread Red Copper/PA66 Hole Pitch 33*33

应用领域 Application Areas

- 启停电源与通讯连接传输
- Start-stop power and communication connection transmission

产品功能特点 Product Points

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|----------------|--------------------------|---------------|
| • 额定电流: | 500A | • 端子接线方式: | 锁螺丝 |
| • Rated current: | 500A | • Terminal Connection: | Locking screw |
| • 额定电压: | 600V DC | • 盐雾测试: | 48 H |
| • Rated voltage: | 600V DC | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥500MΩ | • 耐电压 : | 1000V DC |
| • Insulation resistance: | ≥500MΩ | • Withstand voltage : | 1000V DC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥3000 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥3000 cycles |
| • 使用环境: | -40°C ~ +105°C | • 中心孔紧固力: | ≥9N Max |
| • Operating temperature: | -40°C ~ +105°C | • Locking force: | ≥9N Max |
| • 防护等级: | N/A | • 环保等级: | RoHS |
| • IP grade: | N/A | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



开孔尺寸
Hole Size

推荐面板安装尺寸

Recommended Panel Mounting Dimensions

[HLK-224 download online
www.honlix.com](http://www.honlix.com)

HLK-225

- 方形 300A 单螺纹 紫铜/PA66 孔距33*33
- Square 300A Signal Thread Red Copper/PA66 Hole Pitch 33*33

应用领域 Application Areas

- 储能电源与通讯连接传输
- Energy storage power supply and signal connection transmission

产品功能特点 Product Points

- 支持瞬间大电流使用场景
- Supports instantaneous high current usage scenarios
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size

技术参数 Technical Data

- 额定电流: 300A
- Rated current: 300A
- 额定电压: 600V DC
- Rated voltage: 600V DC
- 绝缘电阻: $\geq 500M\Omega$
- Insulation resistance: $\geq 500M\Omega$
- 阻燃等级: UL94V-0
- Flame retardant rating: UL94V-0
- 使用环境: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- 防护等级: N/A
- IP grade: N/A


- 端子接线方式: 锁螺丝
- Terminal Connection: Locking screw
- 盐雾测试: 48 H
- Salt spray resistance: 48 H
- 耐电压: 1000V DC
- Withstand voltage: 1000V DC
- 机械寿命: ≥ 3000 次
- Flame retardant rating: ≥ 3000 cycles
- 中心孔紧固力: $\geq 9\text{N}$ Max
- Locking force: $\geq 9\text{N}$ Max
- 环保等级: RoHS
- Environmental grade: RoHS

商务条款 Terms of business


- 起订量: 1 pcs
- MOQ: 1 pcs
- 交货周期: 2周 (紧急订单1周)
- L/T: 2 weeks

- 交货条款: Ex works
- Terms of delivery: Ex works
- 海关编码: 854422100
- HS code: 854422100

产品尺寸 Product dimension



HLK-225 download online
www.honlix.com



推荐面板安装尺寸

Recommended Panel Mounting Dimensions

HONLIX

为储能提供创新连接解决方案

Innovative connectivity solutions for energy storage

Honlix Inc.

Tel: +86-0512-57445295

Fax: +86-0512-57440096

E-mail: info@honlix.com

http: www.honlix.com

Zip code: 215 300

Add: No 570, Dewang Road, Zhangpu Town, Kunshan City, Jiangsu Province, China.