

3 系_电动自行车连接解决方案
3 Series_E-bike Connectivity Solutions



公司简介

Company Profile

弘林科创建于2015年，是全球知名的大功率连接器整体方案提供商，拥有ISO9001, ISO14001, IATF16949管理体系认证，通过了CE RoHS REACH等国际测试认证，同时也获得中国国家知识产权局授权专利约30项左右，是中国国家科技型创新企业，弘林科在全球拥有2个制造工厂（分别位于中国昆山/河南南阳），5个销售公司（中国/日本/泰国/韩国/美国）

弘林科拥有资深专业的模具设计加工，自动化制造能力，完整的检测设备及技术，打造全球一流的连接器品牌，服务全球用户；同时我们具有强大的定制化能力，依据不同客户的差异化需求，提供专业，高效，快捷的定制化连接解决方案，为顾客创造价值。

弘林科专注于新能源连接器，其中1系_M5/M8/M12/M16圆型连接器，2系_储能连接器，3系_电动自行车连接器，4系_电动工具连接器，5系_电动摩托车连接器，6系_电动汽车充电枪/座，7系充电桩及放电枪等一站式解决方案。

Founded in 2015, Honlix is a world-renowned total solution provider of high power connectors with ISO9001, ISO14001, IATF16949 management system certification, passed CE RoHS REACH and other international testing and certification, and also obtained about 30 patents authorized by China National Intellectual Property Patent Office, which is a national science and technology-based innovative enterprise in China.

Honlix has 2 manufacturing factories (located in Kunshan, China / Nanyang, Henan Province) and 5 sales companies (China / Japan / Thailand / Korea / USA)

Honlix has experienced and professional mold design and processing, automated manufacturing capabilities, complete testing equipment and technology to build a global first-class connector brand to serve the global user; at the same time, we have a strong ability to customize, according to the different customer needs, to provide professional, efficient, and effective connectors to meet different needs. At the same time, we have a strong customization ability, according to the differentiated needs of different customers, to provide professional, efficient, fast customized connection solutions, to create value for customers.

Honlix specializes in new energy connectors, including Series 1_M5/M8/M12/M16 circular connectors, Series 2_energy storage connectors, Series 3_electric bicycle connectors, Series 4_electric tool connectors, Series 5_electric motorcycle connectors, Series 6_electric vehicle charging guns/mounts, Series 7 charging piles and discharging guns, and other one-stop solutions.

Honlix's New HQ



Ownership of Honlix's HQ buliding

公司简介 Company Profile

HONLIX



昆山工厂
Kunshan Factory



河南工厂
Henan Factory


资质证书 Certificates



ISO90001



ISO14000



TS16949



CE



RoHS



CE



Utility model patents



Appearance Patent



EIA report

全球服务 Global Services



1. Kunshan, China_factory
2. Henan, China_factory
3. Shanghai, China_office
4. Yokohama, Japan_office
5. Seoul, Korea_office
6. California, USA_office
7. Bangkok, Thailand_office

1. 中国昆山_工厂
2. 中国河南_工厂
3. 中国上海_销售办公室
4. 日本横滨_销售办公室
5. 韩国首尔_销售办公室
6. 美国加州_销售办公室
7. 泰国曼谷_销售办公室

电动自行车连接器应用 E-bike Connectors Application

Motor



Battery Charging



Battery Discharging



Brake/Speaker/Display/Light



3系_产品目录

3 Series_Contents

1. M8 Serice Signal Connector M8系列通讯防水连接器

HLK-301 M8 2PIN Male	1
HLK-302 M8 2PIN Female	2
HLK-303 M8 3PIN Male	3
HLK-304 M8 3PIN Female	4
HLK-305 M8 4PIN Male	5
HLK-306 M8 4PIN Female	6
HLK-307 M8 5PIN Male	7
HLK-308 M8 5PIN Female	8
HLK-309 M8 6PIN Male	9
HLK-310 M8 6PIN Female	10
HLK-311 M8 7PIN Male	11
HLK-312 M8 7PIN Female	12
HLK-313 M8 8PIN Male	13
HLK-314 M8 8PIN Female	14

2. Z Serice Power Connector Z系列电源防水连接器

HLK-315 M8 2PIN Male	15
HLK-316 M8 2PIN Female	16

3. 3+6 Motor Connector 3+6电机防水连接器

HLK-317 3+6PIN Male 15A	17
HLK-318 3+6PIN Female 15A	18

4. Flat Waterproof Splitter 分流器 2 to 4

HLK-319 2 to 4	19
----------------	----

5. DC 5521 Charging Connector DC5521充电连接器

HLK-320 DC5521 Male 15A	20
HLK-321 DC5521 Female 15A	21

6. 25A 6PIN Connector 底插连接器

HLK-322 25A 6 PIN Male 90 Degree	22
HLK-323 25A 6PIN Female	23

3系_产品目录

3 Series_Contents

7. 15A 3PIN Connectors for BOSCH 博士电动自行车充电连接器

HLK-325 2+3 PIN Male 10A -----24

8. 10A 2+3PIN Underslot Connector 10A 2+3PIN 底插连接器

HLK-325 2+3 PIN Male 10A -----25

HLK-328 2+3 PIN Female 10A -----28

9. M8 Serice Power*2PIN+Signal*2PIN M8 2PIN*Power+2PIN*Signal

HLK-326 M8 2PIN+2PIN Male -----26

HLK-327 M8 2PIN+2PIN Female -----27

HLK-301

- M8 2PIN 公 连接器
- M8 2PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size

技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-301 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-302

- M8 2PIN 母 连接器
- M8 2PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-302 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-303

- M8 3PIN 公 连接器
- M8 3PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-303 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-304

- M8 3PIN 母 连接器
- M8 3PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-304 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-305

- M8 4PIN 公 连接器
- M8 4PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-305 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-306

- M8 4PIN 母 连接器
- M8 4PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size


技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-306 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-307

- M8 5PIN 公 连接器
- M8 5PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-307 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-308

- M8 5PIN 母 连接器
- M8 5PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-308 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-309

- M8 6PIN 公 连接器
- M8 6PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-309 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-310

- M8 6PIN 母 连接器
- M8 6PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-310 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-311

- M8 7PIN 公 连接器
- M8 7PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-311 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-312

- M8 7PIN 母 连接器
- M8 7PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size


技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-312 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-313

- M8 8PIN 公 连接器
- M8 8PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	信号2A	• 端子接线方式:	焊接
• Rated current:	Signal 2A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-313 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-314

- M8 8PIN 母连接器
- M8 8PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 信号2A | • 端子接线方式: | 焊接 |
| • Rated current: | Signal 2A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-314 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-315



- Z系 2PIN 公连接器
- Z Series 2PIN male connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 电源10A | • 端子接线方式: | 焊接 |
| • Rated current: | Power 10A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-315 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-316



- Z系 2PIN 母连接器
- Z Series 2PIN female connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

• 额定电流:	电源10A	• 端子接线方式:	焊接
• Rated current:	Power 10A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-316 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-317

- 3+6PIN 15A 公 电机连接器
- 3+6PIN 15A male motor connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|--------------------------|--------------------------|-------------|
| • 额定电流: | 电源15A*2+通讯2A*6 | • 端子接线方式: | 焊接 |
| • Rated current: | Power 15A*2+ Signal 2A*6 | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-317 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-318

- 3+6PIN 15A 母 电机连接器
- 3+6PIN 15A female motor connector

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

• 额定电流:	电源15A*2+通讯2A*6	• 端子接线方式:	焊接
• Rated current:	Power 15A*2+ Signal 2A*6	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



HLK-319

- 2 to 4 扁形防水分线
- 2 to 4 Flat waterproof splitter

应用领域 Application Areas

- 电动自行车通讯连接传输
- E-bike communication transmission

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

• 额定电流:	N/A	• 端子接线方式:	焊接
• Rated current:	N/A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-319 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-320

- DC 5521 公 连接器 15A
- DC 5521 Male connectors 15A

应用领域 Application Areas

- 电动自行车电池充电连接器
- E-bike Battery Charging Connector

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size





技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 电源15A | • 端子接线方式: | 焊接 |
| • Rated current: | Power 15A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP45 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP45 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-320 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-321

- DC 5521 母 连接器 15A
- DC 5521 Female connectors 15A

应用领域 Application Areas

- 电动自行车电池充电连接器
- E-bike Battery Charging Connector

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 电源15A | • 端子接线方式: | 焊接 |
| • Rated current: | Power 15A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP45 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP45 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-321 download online
honlix.com](http://honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-322


- 25A 6PIN电池连接器 90度弯头 公
- 25A 6PIN male battery connector 90 degrees

应用领域 Application Areas

- 电动自行车电池放电连接器
- E-bike Battery Discharging Connector

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size






技术参数 Technical Data

• 额定电流:	电源25A	• 端子接线方式:	焊接
• Rated current:	Power 25A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP45 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP45 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



推荐面板安装尺寸
Recommended Panel Mounting Dimensions

[HLK-322 download online
honlix.com](https://www.honlix.com)

HLK-323

- 25A 6PIN电池连接器 母
- 25A 6PIN female battery connector 90 degrees

应用领域 Application Areas

- 电动自行车电池放电连接器
- E-bike Battery Discharging Connector

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size






技术参数 Technical Data

• 额定电流:	电源25A	• 端子接线方式:	焊接
• Rated current:	Power 25A	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP45 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP45 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



推荐面板安装尺寸
Recommended Panel Mounting Dimensions

[HLK-323 download online
honlix.com](http://honlix.com)

HLK-324

- 15A 3PIN BOSCH 电自充电连接器 公
- 15A 3PIN BOSCH E-bikes charging connector male

应用领域 Application Areas

- 博士电动自行车电池放电连接器
- BOSCH E-bike Battery Discharging Connector

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size



技术参数 Technical Data

- | | | | |
|--------------------------|-----------------------|--------------------------|-------------|
| • 额定电流: | 电源 15A | • 端子接线方式: | 焊接 |
| • Rated current: | Power 15A | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP45 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP45 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



HLK-325

- 10A 2+3PIN 充电连接器 母
- 10A 2+3PIN charging connector female

应用领域 Application Areas

- 智租换电定制充电连接器
- Customized charging connector for ZZ

产品功能特点 Product Points

- 防水IP45
- IP45 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	电源 10A*2PIN+通讯2A*3PIN	• 端子接线方式:	焊接
• Rated current:	Power 10A*2PIN+Signal 2A*3PIN	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP45 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP45 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-325 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-326

- M8系列电源15A*2PIN+通讯2A*2PIN 公
- M8 Series Power15A&Signal 2A 2+2PIN Male

应用领域 Application Areas

- 电动自动车电源与通讯连接传输
- Power and Signal Connection Transmission for e-bikes

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

• 额定电流:	电源 15A*2PIN+通讯2A*2PIN	• 端子接线方式:	焊接
• Rated current:	Power 15A*2PIN+Signal 2A*2PIN	• Terminal Connection:	Soldering
• 额定电压:	AC 200V 50Hz 1分钟无击穿	• 盐雾测试:	48 H
• Rated voltage:	AC 200V 50Hz 1 minute	• Salt spray resistance	48 H
• 绝缘电阻:	≥10MΩ	• 耐电压 :	500V AC
• Insulation resistance:	≥10MΩ	• Withstand voltage :	500V AC
• 阻燃等级:	UL94V-0	• 机械寿命:	≥200 次
• Flame retardant rating	UL94V-0	• Flame retardant rating	≥200 cycles
• 使用环境:	-40°C ~ +105°C	• 拔出力:	≥3N
• Operating temperature:	-40°C ~ +105°C	• Pull-out force:	≥3N
• 防护等级:	IP67 (公母互配后)	• 环保等级:	RoHS
• IP grade:	IP67 (mated)	• Environmental grade:	RoHS

商务条款 Terms of business

• 起订量:	1 pcs	• 交货条款:	Ex works
• MOQ	1 pcs	• Terms of delivery:	Ex works
• 交货周期:	2周 (紧急订单1周)	• 海关编码:	854422100
• L/T	2 weeks	• HS code:	854422100

产品尺寸 Product dimension



[HLK-326 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HLK-327

- M8系列电源15A*2PIN+通讯2A*2PIN 母
- M8 Series Power15A&Signal 2A 2+2PIN female

应用领域 Application Areas

- 电动自行车电源与通讯连接传输
- Power and Signal Connection Transmission for e-bikes

产品功能特点 Product Points

- 防水IP67
- IP67 (Mated)
- 快速直接插拔
- Fast direct plugging and unplugging
- 体积小
- Very small in size




技术参数 Technical Data

- | | | | |
|--------------------------|-------------------------------|--------------------------|-------------|
| • 额定电流: | 电源 15A*2PIN+通讯2A*2PIN | • 端子接线方式: | 焊接 |
| • Rated current: | Power 15A*2PIN+Signal 2A*2PIN | • Terminal Connection: | Soldering |
| • 额定电压: | AC 200V 50Hz 1分钟无击穿 | • 盐雾测试: | 48 H |
| • Rated voltage: | AC 200V 50Hz 1 minute | • Salt spray resistance | 48 H |
| • 绝缘电阻: | ≥10MΩ | • 耐电压 : | 500V AC |
| • Insulation resistance: | ≥10MΩ | • Withstand voltage : | 500V AC |
| • 阻燃等级: | UL94V-0 | • 机械寿命: | ≥200 次 |
| • Flame retardant rating | UL94V-0 | • Flame retardant rating | ≥200 cycles |
| • 使用环境: | -40°C ~ +105°C | • 拔出力: | ≥3N |
| • Operating temperature: | -40°C ~ +105°C | • Pull-out force: | ≥3N |
| • 防护等级: | IP67 (公母互配后) | • 环保等级: | RoHS |
| • IP grade: | IP67 (mated) | • Environmental grade: | RoHS |

商务条款 Terms of business

- | | | | |
|---------|-------------|----------------------|-----------|
| • 起订量: | 1 pcs | • 交货条款: | Ex works |
| • MOQ | 1 pcs | • Terms of delivery: | Ex works |
| • 交货周期: | 2周 (紧急订单1周) | • 海关编码: | 854422100 |
| • L/T | 2 weeks | • HS code: | 854422100 |

产品尺寸 Product dimension



[HLK-327 download online
honlix.com](https://www.honlix.com)

推荐面板安装尺寸
Recommended Panel Mounting Dimensions

HONLIX

为电自提供创新连接解决方案

Innovative connectivity solutions for e-bikes

Honlix Inc.

Tel: +86-0512-57445295

Fax: +86-0512-57440096

E-mail: info@honlix.com

http://www.honlix.com

Zip code: 215 300

Add: No 570, Dewang Road, Zhangpu Town, Kunshan City, Jiangsu Province, China.